

#### **SECTION 4 - FIRST AID MEASURES**

FIRST AID PROCEDURES: INHALATION: Remove to fresh air. Restore normal breathing. Treat symptomatically. See physician. SKIN: Wash thoroughly with soap and water. Remove contaminated clothing. Consult physician if irritation persists. EYES: Flush immediately with plenty of water for at least 15 minutes and get medical attention. INGESTION: Drink 1 or 2 glasses of water to dilute. Never give anything by mouth to an unconscious person. Do not induce vomiting. Consult physician or poison control center IMMEDIATELY. Treat symptomatically.

#### **SECTION 5 - FIRE FIGHTING MEASURES**

FLASH POINT: 207 F (SETA) LOWER EXPLOSIVE LIMIT: N.A.  
UPPER EXPLOSIVE LIMIT: N.A.

FLAMMABILITY - OSHA: COMBUSTIBLE - CLASS IIIB  
DOT: NOT REGULATED

EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL

LOWEST FLASHING SOLVENT:

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat and pressure buildup. May produce a floating fire hazard. Isolate from electrical equipment, sparks, heat and open flame. Vapors may spread long distances, cause flash fire or ignite explosively.

FIREFIGHTING PROCEDURES: Wear full protective equipment, self-contained breathing apparatus. Water may be used to cool closed containers to prevent pressure build-up or explosion when exposed to extreme heat.

#### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

SPILL, LEAKS: Remove all sources of ignition. Avoid breathing vapors. Ventilate area. Use absorbent, inert cleanup materials. (DO NOT use sawdust.) Remove absorbent material with non-sparking tools. Place in separate container. Keep out of sewers and waterways. If entry is threatened or occurs, notify local authorities.

#### **SECTION 7 - HANDLING AND STORAGE**

HANDLING AND STORAGE: Keep container closed, upright when not in use. Store in cool, dry, well-ventilated area. Avoid prolonged storage temperatures above 100F. Use caution when pouring. Avoid breathing sanding dust. Do not weld or flame cut on empty container.

#### **SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

VENTILATION: Implement administrative and engineering controls to reduce exposure. Provide sufficient ventilation in volume and pattern to keep air contaminant concentrations below the TLV limits. Remove welding or flame cutting decomposition products; follow current, ANSI Z49.1, "Safety in Welding and Cutting". Refer to 29 CFR parts 1910 and 1915, for coating operations; part 1910.146, Confined Spaces.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA certified respirator designed to remove a combination of particulates (dust or spray mist) and vapor. When